



SAFETY DATA SHEET

SCIGRIP® SG5000-40 AMBER

Page: 1

Compilation date: 06/04/2011

Revision date: 10/12/2015

Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SCIGRIP® SG5000-40 AMBER

Product code: SG5000-40-A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Scigrip Adhesives Ltd

Unit 22 Bentall Business Park

Glover Road

Washington

Tyne & Wear

NE37 3JD

England

Tel: +44(0)191 419 6444

Fax: +44(0)191 419 6445

Email: technical.supportuk@scigrip.com

1.4. Emergency telephone number

Emergency tel: CHEMTEL Tel: 813-248-0573 (International)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; STOT SE 3: H335; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

[cont...]

SAFETY DATA SHEET

SCIGRIP® SG5000-40 AMBER

Page: 2

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS05: Corrosion

GHS07: Exclamation mark



Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261: Avoid breathing vapours.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333+313: If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

METHYL METHACRYLATE - REACH registered number(s): 01-2119452498-28-000, 01-2119452498-28-0025, 01-2119452498-28-0028

EINECS	CAS	PBT / WEL	CLP Classification	Percent
201-297-1	80-62-6	-	Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317	50-75%

2-METHYLPROPENOIC ACID - REACH registered number(s): 01-2119463884-26-0000

201-204-4	79-41-4	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1A: H314	1-5%
-----------	---------	---	--	------

3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYRIDINE

252-091-3	34562-31-7	-	Acute Tox. 4: H302+312; Aquatic Chronic 4: H413; Skin Irrit. 2: H315; Eye Irrit. 2: H319	1-5%
-----------	------------	---	--	------

[cont...]

SAFETY DATA SHEET

SCIGRIP® SG5000-40 AMBER

Page: 3

2,6-BIS(1,1-DIMETHYLETHYL)-4-METHYL PHENOL

204-881-4	128-37-0	-	Aquatic Acute 1: H400; Aquatic Chronic 1: H410	1-5%
-----------	----------	---	--	------

CUMENE HYDROPEROXIDE

201-254-7	80-15-9	-	Org. Perox. EF: H242; Acute Tox. 3: H331; Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Skin Corr. 1B: H314	<1%
-----------	---------	---	--	-----

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY

265-185-4	64742-82-1	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; Aquatic Chronic 2: H411	<1%
-----------	------------	---	--	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

[cont...]

SAFETY DATA SHEET
SCIGRIP® SG5000-40 AMBER

Page: 4

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

METHYL METHACRYLATE

[cont...]

SAFETY DATA SHEET

SCIGRIP® SG5000-40 AMBER

Page: 5

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	203mg/m ³	416mg/m ³	-	-

2-METHYLPROPENOIC ACID

UK	72 mg/m ³	143 mg/m ³	-	-
----	----------------------	-----------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Amber

Odour: Characteristic odour

Viscosity: Viscous

Flash point °C: 15

Relative density: 0.97

9.2. Other information

Other information: Flammability based on data for methyl methacrylate

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

[cont...]

SAFETY DATA SHEET
SCIGRIP® SG5000-40 AMBER

Page: 6

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

METHYL METHACRYLATE

DERMAL	RBT	LD50	>5000	mg/kg
INHALATION	RAT	4H LC50	29.8	mg/l
ORAL	RAT	LD50	>5000	mg/kg

2-METHYLPROPENOIC ACID

DERMAL	RBT	LD50	500-1000	mg/kg
ORAL	RAT	LD50	1320	mg/kg
VAPOURS	RAT	1H LC50	7.1	mg/l

3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYRIDINE

DERMAL	RBT	LD50	>1000	mg/kg
ORAL	RAT	LD50	>500	mg/kg

2,6-BIS(1,1-DIMETHYLETHYL)-4-METHYL PHENOL

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2930	mg/kg

CUMENE HYDROPEROXIDE

ORL	MUS	LDLO	5	gm/kg
ORL	RAT	LD50	382	mg/kg
SCU	RAT	LD50	382	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

[cont...]

SAFETY DATA SHEET

SCIGRIP® SG5000-40 AMBER

Page: 7

STOT-single exposure	INH	Hazardous: calculated
----------------------	-----	-----------------------

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

METHYL METHACRYLATE

DAPHNIA MAGNA	48H EC50	69	mg/l
GREEN ALGA (<i>Selenastrum capricornutum</i>)	72H EC50	>110	mg/l
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	>79	mg/l

2-METHYLPROPENOIC ACID

Daphnia magna	48H EC50	>130	mg/l
GREEN ALGA (<i>Selenastrum capricornutum</i>)	96H ErC50	45	mg/l
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	85	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

[cont...]

SAFETY DATA SHEET

SCIGRIP® SG5000-40 AMBER

Page: 8

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: This product is a Seveso category/named substance in Annex I of Council Directive 96/82/EC.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Methacrylates have a perceptible or distinctive odour to which the human nose is very sensitive even when well below the TLV limits. The smell can be identified well below ranges of less than 0.5 ppm parts per million in a well-ventilated area.

ABBREVIATIONS

PBT - Persistent Bioaccumulative Toxic

VOC - Volatile Organic Content

[cont...]

SAFETY DATA SHEET

SCIGRIP® SG5000-40 AMBER

Page: 9

STP - Sewage Treatment Plant
LC0 - Maximum Sublethal Concentration
LC50 - Lethal Concentration 50%
LD50 - Lethal Dose 50%
PNEC - Predicted No Effect Concentration
DNEL - Derived No Effect Level
OPT - Ophthalmic
ING - Ingestion
ORL - Oral
DRM - Dermal
INH - Inhalation
MUS - Mouse
RBT - Rabbit

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H242: Heating may cause a fire.
H302: Harmful if swallowed.
H302+312: Harmful if swallowed or in contact with skin.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H331: Toxic if inhaled.
H335: May cause respiratory irritation.
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.
H413: May cause long lasting harmful effects to aquatic life.

Legal disclaimer: This company shall not be held liable for any damage resulting from handling or from contact with the above product.